



# ConTExT

commands

# EN



# ConTeXt

## commands

en / english

November 21, 2009



\about {<sup>1</sup>.} [<sup>2</sup>.]

- 1 CONTENT
- 2 REFERENCE

\adaptlayout [...,<sup>1</sup>...] [...,<sup>2</sup>.,...]

- 1 NUMBER OPTIONAL
- 2 height = DIMENSION max
- lines = NUMBER

\startalignment [...,\*...] ... \stop

- \* inherits from \setupalign

\appendix [...,<sup>1</sup>...] {<sup>2</sup>.}

- 1 REFERENCE OPTIONAL
- 2 CONTENT

\at {<sup>1</sup>.} {<sup>2</sup>.} [...<sup>3</sup>.]

- 1 CONTENT
- 2 CONTENT
- 3 REFERENCE

\atpage [...]

- \* REFERENCE

\startbackground {...} ... \stop

- \* CONTENT

\blackrule [...,\*,...]

- \* inherits from \setupblackrules

\blackrules [...,\*,...]

- \* inherits from \setupblackrules

\blank [...,\*,...]

- \* small medium big nowhite back white disable force reset line halfline FORMULA fixed flexible none always outer joinedup

\bookmark [<sup>1</sup>.] {<sup>2</sup>.}

- 1 IDENTIFIER OPTIONAL
- 2 CONTENT

\startbuffer [...] ... \stop

- \* IDENTIFIER OPTIONAL

\startbuffer [...] ... \stopbuffer

- \* IDENTIFIER OPTIONAL

\but [...]

- \* REFERENCE

\button [...,<sup>1</sup>...] {<sup>2</sup>.} [...<sup>3</sup>,...]

- 1 inherits from \setupbuttons
- 2 CONTENT
- 3 REFERENCE

\bypassblocks [...,<sup>1</sup>...] [...,<sup>2</sup>,...]

- 1 IDENTIFIER OPTIONAL
- 2 IDENTIFIER

\cap {...}  
 \* CONTENT

```
\chapter [...1,...] {..2}
1  REFERENCE  OPTIONAL
2  CONTENT
```

```
\character {...}  
*   CONTENT
```

```
\characters {...}
*   CONTENT
```

```
\chem {.1.} {.2.} {.3.}
1  CONTENT
2  CONTENT
3  CONTENT
```

```
\clip [...,1...] {2...}
1 inherits from \setupclipping
2 CONTENT
```

```
\clonefield [.1.] [...,2...] [...,3.] [...,4...]
1 IDENTIFIER
2 IDENTIFIER
3 IDENTIFIER
4 IDENTIFIER
```

```
\startcolor [...] ... \stop
* IDENTIFIER
```

\column

```
\startcolumns [...,*,...] ... \stop
* inherits from \setupcolumns
```

```
\startcombination [...] ... \stop
* N*M
```

```
\startcomment [.1.] [....2...] ... \stop
1 IDENTIFIER      OPTIONAL      OPTIONAL
2 inherits from \setupcomment
```

```
\comparecolorgroup [...]  
* IDENTIFIER
```

```
\comparepalet [...]  
* IDENTIFIER
```

```
\completenesscombinedlist [..1.] [...,2.,...]  
1 IDENTIFIER                                OPTIONAL  
2 inherits from \setupcombinedlist
```

```
\completelistoffloats
```

\completelistofsorts

`\completelistofsynonyms`

`\completeregister [...,*,...]`  
\* inherits from \setupregister OPTIONAL

`\startcomponent ... \stop`  
\* FILE NAME

`\convertnumber {.1.} {.2.}`  
1 CONTENT  
2 CONTENT

`\copyfield [.1.] [...2,...]`  
1 IDENTIFIER  
2 IDENTIFIER

`\correctwhitespace {...}`  
\* CONTENT

`\coupledocument [.1.] [.2.] [.3.]`  
1 IDENTIFIER  
2 file  
3 IDENTIFIER

`\coupleddregister [.1.] {.2.}`  
1 TEXT OPTIONAL  
2 INDEX

`\couplemarking [.1.] [.2.]`  
1 IDENTIFIER  
2 IDENTIFIER

`\couplepage [...1,...] [...,2.,...]`  
1 IDENTIFIER  
2 option = doublesided  
before = COMMAND  
after = COMMAND

`\couplepaper [...]`  
\* IDENTIFIER

`\coupleregister [...]`  
\* IDENTIFIER

`\crlf`

`\currentdate [...*,...]`  
\* inherits from \date

`\currenttheadnumber`

`\Cap {...}`  
\* CONTENT

`\Caps {...*...}`  
\* WORD

```
\CAP {...}  
*   CONTENT
```

```
\Character {...}  
*   CONTENT
```

```
\Characters {...}  
*   CONTENT
```

```
\date [...,1...,...][...2,...]
1  d = NUMBER OPTIONAL
   m = NUMBER
   y = NUMBER
2  day month year weekday d m y w dd mm yy space -- day+ d+ dd+ referral TEXT
```

```
\decouplemarking [...]  
*   IDENTIFIER
```

```
\define [1.] \2. {3.}  
1  NUMBER OPTIONAL  
2  CSNAME  
3  CONTENT
```

```
\defineblank [1.] [2.]  
1  IDENTIFIER  
2  inherits from \setupblank
```

```
\defineblock [...]  
*   IDENTIFIER
```

```
\definebodyfont [...,1,...] [2.] [...,3...,...]
1  5pt ... 12pt small big OPTIONAL
2  rm ss tt hw cg mm
3  tf = FILE
   bf = FILE
   sl = FILE
   it = FILE
   bs = FILE
   bi = FILE
   sc = FILE
   mr = FILE
   ex = FILE
   mi = FILE
   sy = FILE
   ma = FILE
   mb = FILE
   mc = FILE
   md = FILE
```

```
\definebodyfont [1.] [2.] [3.]  
1  IDENTIFIER  
2  inherits from \setupbodyfont  
3  inherits from \setupbodyfont
```



```

\definebodyfontenvironment [.1.] [.2.] [...,3,...]
1 IDENTIFIER OPTIONAL OPTIONAL
2 5pt ... 12pt default
3 text = DIMENSION
  script = DIMENSION
  scriptscript = DIMENSION
  x = DIMENSION
  xx = DIMENSION
  a = DIMENSION
  b = DIMENSION
  c = DIMENSION
  d = DIMENSION
  small = DIMENSION
  big = DIMENSION
  interlinespace = DIMENSION
  em = normal bold slanted boldslanted type cap small... COMMAND

```

```

\definebodyfont [.1.] [.2.] [.3.]
1 inherits from \setupbodyfont
2 inherits from \setupbodyfont
3 IDENTIFIER

```

```

\definebuffer [.*.]
* IDENTIFIER

```

```

\definecolor [.1.] [...,2,...]
1 IDENTIFIER
2 r = TEXT
  g = TEXT
  b = TEXT
  c = TEXT
  m = TEXT
  y = TEXT
  k = TEXT
  s = TEXT
  h = TEXT
  t = TEXT
  a = TEXT
  p = TEXT
  e = TEXT

```

```

\definecolorgroup [.1.] [.2.] [x:y:3=,...]
1 IDENTIFIER OPTIONAL
2 rgb cmyk gray s
3 TRIPLET

```

```

\definecombinedlist [.1.] [...,2,...] [...,3,...]
1 IDENTIFIER OPTIONAL
2 LIST
3 inherits from \setupcombinedlist

```

```

\defineconversion [.1.] [.2.]
1 IDENTIFIER
2 COMMAND TEXT

```

```

\definedescription [.1.] [...,2,...]
1 IDENTIFIER OPTIONAL
2 inherits from \setupdescriptions

```

```

\definedfont [.*.]
* inherits from \definefont

```

```

\defineenumeration [...,1,...] [.2.] [...,3,...]
1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 inherits from \setupenumerations

```

```
\definefield [1.] [2.] [3.] [...4,...] [5.]
1 IDENTIFIER OPTIONAL
2 text line push check radio combo choice popup
3 IDENTIFIER
4 IDENTIFIER
5 IDENTIFIER
```

```
\definefieldstack [1.] [...2,...] [...3,...]
1 IDENTIFIER
2 IDENTIFIER
3 inherits from \setupfields
```

```
\definefiguresymbol [1.] [2.] [...3,...]
1 IDENTIFIER OPTIONAL
2 TEXT
3 inherits from \setuexternalfigures
```

```
\definefloat [1.] [2.]
1 SINGULAR NAME
2 PLURAL NAME
```

```
\definefont [1.] [2.] [3.]
1 IDENTIFIER OPTIONAL
2 FILE
3 TEXT
```

```
\definefontfeature [1.] [2.] [3.]
1 TEXT OPTIONAL
2 IDENTIFIER
3 compose = no yes
mode = node base
tlig = no yes
trep = no yes
script = IDENTIFIER
language = IDENTIFIER
..tag.. = no yes
```

```
\definefonthandling [1.] [2.] [3.]
1 IDENTIFIER
2 IDENTIFIER
3 type = hanging hz spacing tag
right = NUMBER
left = NUMBER
factor = NUMBER
min = NUMBER
max = NUMBER
step = NUMBER
```

```
\definefontsynonym [1.] [2.] [3.]
1 TEXT OPTIONAL
2 IDENTIFIER
3 encoding = IDENTIFIER
features = IDENTIFIER
handling = IDENTIFIER
mapping = IDENTIFIER
```

```
\defineframed [1.] [...2,...]
1 IDENTIFIER OPTIONAL
2 inherits from \setupframedtexts
```

```
\defineframedtext [1.] [...2,...]
1 IDENTIFIER OPTIONAL
2 inherits from \setupframedtexts
```

```
\definehead [1.] [2.]
1 IDENTIFIER
2 SECTION
```

`\defineindenting [.1.] [...,2.,...]`

1 IDENTIFIER  
2 *inherits from* \setupindentations

`\defineinteractionmenu [...,1,...] [...,2.,...]`

1 left right top bottom IDENTIFIER OPTIONAL  
2 *inherits from* \setupinteractionmenu

`\defineinteractionmenu [.1.] [.2.] [...,3.,...]`

1 left right top bottom IDENTIFIER OPTIONAL OPTIONAL  
2 left right top bottom IDENTIFIER  
3 *inherits from* \setupinteractionmenu

`\definelabel [.1.] [...,2.,...]`

1 IDENTIFIER  
2 text = TEXT  
location = inmargin intext  
way = bytext bycd:section  
blockway = yes no  
headstyle = normal bold slanted boldslanted type cap small... COMMAND  
headcolor = IDENTIFIER  
before = COMMAND  
after = COMMAND

`\definelist [.1.] [.2.] [...,3.,...]`

1 IDENTIFIER OPTIONAL OPTIONAL  
2 IDENTIFIER  
3 *inherits from* \setuplist

`\definelogo [.1.] [.2.] [.3.] [...,4.,...]`

1 IDENTIFIER  
2 top header footer bottom  
3 none page leftedge leftmargin left middle right rightmargin rightedge  
4 command = COMMAND TEXT  
state = start stop

`\definemakeup [.1.] [...,2.,...]`

1 IDENTIFIER  
2 *inherits from* \setupmakeup

`\definemarking [.1.] [.2.]`

1 IDENTIFIER OPTIONAL  
2 IDENTIFIER

`\defineoutput [.1.] [...2,...]`

1 IDENTIFIER  
2 IDENTIFIER

`\defineoverlay [...,1,...] [.2.]`

1 IDENTIFIER  
2 COMMAND

`\definepalet [.1.] [...,2.,...]`

1 IDENTIFIER  
2 IDENTIFIER = IDENTIFIER

`\definepapersize [.1.] [...,2.,...]`

1 IDENTIFIER  
2 width = DIMENSION  
height = DIMENSION  
offset = DIMENSION  
scale = NUMBER

```

\defineparagraphs [..1.] [...,2,...]
1 IDENTIFIER
2 n = NUMBER
  rule = on off
  height = fit DIMENSION
  before = COMMAND
  after = COMMAND
  inner = COMMAND
  distance = DIMENSION
  tolerance = verystRICT STRICT tolerant verytolerant stretch
  align = inner outer left right flushleft flushright middle center normal no yes

```

```

\defineprofile [...,1,...] [...,2,...]
1 IDENTIFIER
2 IDENTIFIER

```

```

\defineprogram [..1.] [..2.] [..3.]
1 IDENTIFIER
2 TEXT
3 TEXT

```

```

\definereference [..1.] [...,2,...]
1 IDENTIFIER
2 REFERENCE

```

```

\definereferenceformat [..1.] [...,2,...]
1 IDENTIFIER
2 left = TEXT
  right = TEXT
  text = TEXT
  label = IDENTIFIER

```

```

\definereferencelist [..1.] [...,2,...]
1 IDENTIFIER OPTIONAL
2 inherits from \setupreferencelist

```

```

\defineregister [..1.] [..2.]
1 SINGULAR NAME
2 PLURAL NAME

```

```

\definesection [..*.]
* IDENTIFIER

```

```

\definesectionblock [..1.] [...,2,...]
1 inherits from \setupsectionblock OPTIONAL
2 inherits from \setupsectionblock

```

```

\definesorting [..1.] [..2.] [..3.]
1 SINGULAR NAME OPTIONAL
2 PLURAL NAME
3 COMMAND

```

```

\definestartstop [..1.] [...,2,...]
1 IDENTIFIER
2 before = COMMAND
  after = COMMAND
  style = normal bold slanted boldslanted type cap small... COMMAND
  commands = COMMAND

```

```

\definesubfield [..1.] [..2.] [...,3,...]
1 IDENTIFIER
2 IDENTIFIER
3 IDENTIFIER

```

`\definesymbol [.1.] [.2.]`

- 1 IDENTIFIER
- 2 TEXT

`\definesynonyms [.1.] [.2.] [.3.] [.4.]`

- 1 SINGULAR NAME
  - 2 PLURAL NAME
  - 3 COMMAND
  - 4 COMMAND
- OPTIONAL

`\definetabletemplate [.1.] [.2.] [.3.] [.4.]`

- 1 IDENTIFIER
  - 2 TEXT
  - 3 TEXT
  - 4 TEXT
- OPTIONAL    OPTIONAL

`\definetabulate [.1.] [.2.] [.3.]`

- 1 IDENTIFIER
  - 2 IDENTIFIER
  - 3 TEXT
- OPTIONAL

`\definetext [.1.] [.2.] [.3.] [.4.] [.5.]`

- 1 IDENTIFIER
  - 2 header footer
  - 3 TEXT
  - 4 TEXT
  - 5 TEXT
- OPTIONAL    OPTIONAL

`\definetype [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setuptype

`\definetypeface [.1.] [.2.] [.3.] [.4.] [.5.] [.6.]`

- 1 TEXT
  - 2 rm ss tt mm hw cg
  - 3 IDENTIFIER
  - 4 IDENTIFIER
  - 5 IDENTIFIER
  - 6 features = IDENTIFIER
- OPTIONAL    OPTIONAL
- rscale = NUMBER
- encoding = IDENTIFIER
- text = IDENTIFIER

`\definetyping [.1.] [...,2,...]`

- 1 *inherits from* \setuptyping
- 2 *inherits from* \setuptyping

`\defineversion [.1.] [...2,...]`

- 1 IDENTIFIER
- 2 NUMBER

`\description {.1.} .2.`

- 1 CONTENT
- 2 NOTHING

`\determineheadnumber [.*.]`

- \* SECTION

`\determinelistcharacteristics [...,1,...] [...,2,...]`

- 1 IDENTIFIER
  - 2 *inherits from* \setuplist
- OPTIONAL

```
\disableinteractionmenu [1...] [2...,...]
1 left right top bottom IDENTIFIER
2 REFERENCE
```

```
\startdocument [...]* ... \stop
* IDENTIFIER
```

```
\emptylines [...]*
* NUMBER
```

```
\enumeration ...*
* NOTHING
```

```
\startenvironment ...* ... \stop
* FILE NAME
```

```
\externalfigure [1...] [2...,...]
1 FILE OPTIONAL
2 inherits from \setupexternalfigures
```

```
\startfact .1 .2 .3 ... \stop
1 NOTHING
2 NOTHING
3 NOTHING
```

```
\field [...]*
* IDENTIFIER
```

```
\fieldstack [1...] [2...,...] [3...,...]
1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 inherits from \setupfields
```

```
\startfigure [1...] [2...] [3...,...] ... \stop
1 IDENTIFIER
2 FILE
3 factor = NUMBER
frame = on off
```

```
\fillinfield [1...] {2.}
1 TEXT OPTIONAL
2 CONTENT
```

```
\fillinline [...,1...,...] .2.
1 inherits from \setupfillinlines
2 NOTHING
```

```
\fillinrules [...,1...,...] {2.} {3.}
1 inherits from \setupfillinrules OPTIONAL
2 CONTENT
3 CONTENT
```

```
\fillintext [...,1...,...] {2.} {3.}
1 inherits from \setupfillinrules OPTIONAL
2 CONTENT
3 CONTENT
```

```
\fitfield [...]*
* IDENTIFIER
```

\fixedspaces

\startfloat text [<sup>1</sup>.] [<sup>2</sup>.] {<sup>3</sup>.} {<sup>4</sup>.} ... \stopfloat  
1 left right high middle low offset tall  
2 REFERENCE  
3 CONTENT  
4 CONTENT

\followprofile {<sup>1</sup>.} [<sup>2</sup>.]  
1 CONTENT  
2 TEXT

\followprofileversion {<sup>1</sup>.} [<sup>2</sup>.] [<sup>3</sup>.]  
1 CONTENT  
2 TEXT  
3 IDENTIFIER

\followversion {<sup>1</sup>.} [<sup>2</sup>.]  
1 CONTENT  
2 TEXT

\footnote [<sup>1</sup>.] {<sup>2</sup>.}  
1 REFERENCE OPTIONAL  
2 CONTENT

\footnotetext [<sup>1</sup>.] {<sup>2</sup>.}  
1 REFERENCE OPTIONAL  
2 CONTENT

\forceblocks [...<sup>1</sup>,...] [...<sup>2</sup>,...] OPTIONAL  
1 IDENTIFIER  
2 IDENTIFIER

\startformula ... \stopformula

\fraction {<sup>1</sup>.} {<sup>2</sup>.}  
1 CONTENT  
2 CONTENT

\framed [...<sup>1</sup>,...] {<sup>2</sup>.}  
1 inherits from \setupframed  
2 CONTENT

\startframedtext [<sup>1</sup>.] [...<sup>2</sup>,...] ... \stopframedtext  
1 left right middle none OPTIONAL OPTIONAL  
2 inherits from \setupframedtexts

\from [...]  
\* REFERENCE

\getbuffer [...]  
\* IDENTIFIER OPTIONAL

\getmarking [<sup>1</sup>.] [<sup>2</sup>.]  
1 IDENTIFIER  
2 first last previous both all current

\godown [...]  
\* DIMENSION

`\goto {...} {...} [...3,...]`

1 CONTENT  
2 CONTENT  
3 REFERENCE

`\gotobox {...} [...2,...]`

1 CONTENT  
2 REFERENCE

`\graycolor [...]`

\* TEXT

`\grid [...,*...]`

\* x = NUMBER  
y = NUMBER  
nx = NUMBER  
ny = NUMBER  
dx = NUMBER  
dy = NUMBER  
xstep = NUMBER  
ystep = NUMBER  
offset = yes no  
factor = NUMBER  
scale = NUMBER  
unit = cm pt em mm ex es in  
location = left middle

`\hairline`

`\head [...,*...]`

\* REFERENCE OPTIONAL

`\headnumber [...]`

\* SECTION OPTIONAL

`\headtext {...}`

\* CONTENT

`\hideblocks [...1,...] [...2,...]`

1 IDENTIFIER OPTIONAL  
2 IDENTIFIER

`\starthiding ... \stop`

`\high {...}`

\* CONTENT

`\hl [...]`

\* NUMBER

`\in {...} {...} [...3]`

1 CONTENT  
2 CONTENT  
3 REFERENCE

`\indentation ...`

\* NOTHING

`\indenting [...,*...]`

\* never none not no yes always first next small medium big normal odd even DIMENSION



```
\inframed [...,1,...] {2.}
1 inherits from \setupinframed
2 CONTENT
```

```
\ininner [...1.] [...2.] {3.}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inleft [...1.] [...2.] {3.}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inline [...*.]
* REFERENCE
```

```
\inmargin [...1.] [...2.] {3.}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inothermargin [...1.] [...2.] {3.}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inouter [...1.] [...2.] {3.}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inright [...1.] [...2.] {3.}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\installlanguage [...,1.] [...,2,...]
1 IDENTIFIER
2 spacing = packed broad
lefthyphenmin = NUMBER
righthyphenmin = NUMBER
state = start stop
leftsentence = COMMAND
rightsentence = COMMAND
leftsubsentence = COMMAND
rightsubsentence = COMMAND
leftquote = COMMAND
rightquote = COMMAND
leftquotation = COMMAND
rightquotation = COMMAND
leftspeech = COMMAND
middlespeech = COMMAND
rightspeech = COMMAND
limittext = TEXT
date = TEXT
compoundhyphen = COMMAND
leftcompoundhyphen = COMMAND
rightcompoundhyphen = COMMAND
default = IDENTIFIER
```

```
\interactionbar [...,*,...]
* inherits from \setupinteractionbar
```

```
\interactionbuttons [...,1,...] [...2,...]
1 inherits from \setupinteractionbar
2 IDENTIFIER
```

```
\startinteractionmenu [...] ... \stop
* IDENTIFIER
```

```
\item [...,*,...]
* REFERENCE OPTIONAL
```

```
\startitemgroup [...1.] [...2,...] [...3,...] ... \stopitemgroup
1 IDENTIFIER OPTIONAL OPTIONAL
2 a A KA n N m r R KR NUMBER continue standard broad serried packed stopper joinedup atmargin inmargin intro columns
text paragraph repeat
3 inherits from \setupitemgroup
```

```
\items [...,1,...] {...2. ...}
1 inherits from \setupitems
2 CONTENT
```

```
\its [...,*,...]
* REFERENCE OPTIONAL
```

```
\keepblocks [...1,...] [...2,...]
1 IDENTIFIER OPTIONAL
2 all IDENTIFIER
```

```
\labeling [...]
* REFERENCE OPTIONAL
```

```
\labels [...]
* IDENTIFIER
```

```
\labeltext {...}
* CONTENT
```

```
\language [...]
* nl fr en uk de es cz ..
```

```
\leftaligned {...}
* CONTENT
```

```
\startlegend [...1.] 2. 3. 4. ... \stop
1 two OPTIONAL
2 NOTHING
3 NOTHING
4 NOTHING
```

```
\startline [...] ... \stop
* REFERENCE
```

```
\startlinecorrection ... \stop
```

```
\startlinenumbering [...] ... \stop
* continue
```

```
\startlines ... \stop
```

```
\listsymbol [...1.] {...2.}
1 IDENTIFIER
2 CONTENT
```

`\loadsorts`

`\loadsynonyms`

`\startlocal ... \stop`

`\startlocalenvironment ... \stop`

`\startlocalfootnotes ... \stop`

`\logfields`

`\lohi [.1.] {..2.} {..3.}`  
1    low    OPTIONAL  
2    CONTENT  
3    CONTENT

`\low {.*}`  
\*    CONTENT

`\mainlanguage [.*]`  
\*    nl fr en uk de es cz ..

`\startmakeup [.1.] [...,..2.,...] ... \stop`  
1    IDENTIFIER                      OPTIONAL  
2    inherits from \setupmakeup

`\mapfontsize [.1.] [..2.]`  
1    DIMENSION  
2    DIMENSION

`\mar [...,1...] {..2.}`  
1    REFERENCE                      OPTIONAL  
2    CONTENT

`\startmarginblock ... \stop`

`\startmarginrule [.*] ... \stop`  
\*    NUMBER

`\margintext [.1.] [..2.] {..3.}`  
1    + - low                      OPTIONAL    OPTIONAL  
2    REFERENCE  
3    CONTENT

`\marking [.1.] {..2.}`  
1    IDENTIFIER  
2    CONTENT

`\markversion`

`\mathematics {.*}`  
\*    CONTENT

`\mediaeval {.*}`  
\*    CONTENT

\midaligned {...}  
\* CONTENT

\mirror {...}  
\* CONTENT

\month {...}  
\* CONTENT

\moveongrid [...\*,...] ~~reset~~  
\* standard top both bottom -top -both -bottom TEXT high middle low page broad fit depth line reset none DIMENSION

\MONTH {...}  
\* CONTENT

\name {...}  
\* CONTENT

\startname *makeup* ... \stopname

\startnarrower [...\*,...] ... \stop  
\* left middle right ~~reset~~ ~~RESET~~ AL-middle -right -none

\nextsection

\nocap {...}  
\* CONTENT

\noheaderandfooterlines

\noindenting

\nolist {...}  
\* CONTENT

\nomarking {...}  
\* CONTENT

\nomoreblocks

\nomorefiles

\nop

\nospace

\note [...]  
\* REFERENCE

\notopandbottomlines

\nowhitespace

`\numbers {...}`  
\* CONTENT

`\startopposite ... \stop`

`\overbar {...}`  
\* CONTENT

`\overbars {...}`  
\* WORD

`\startoverlay {...} {...} ... \stop`  
1 CONTENT  
2 CONTENT

`\overstrike {...}`  
\* CONTENT

`\overstrikes {...}`  
\* WORD

`\startoverview [...,*...] ... \stop`  
\* IDENTIFIER

`\packed`

`\page [...,*...]`  
\* yes makeup no preference bigpreference left right disable last quadruple even odd blank empty reset start stop

`\pagereference [...]`  
\* REFERENCE

`\pagetype [...]`  
\* IDENTIFIER

`\paragraph`

`\part [...,1...] {...}`  
1 REFERENCE  
2 CONTENT

`\periods [...]`  
\* NUMBER

`\placebookmarks [...,1...] [...,2...]`  
1 IDENTIFIER OPTIONAL OPTIONAL  
2 IDENTIFIER all

`\placecombinedlist [...,1] [...,2,...]`  
1 IDENTIFIER OPTIONAL  
2 *inherits from \setupcombinedlist*

`\placecombinedlist [...,1] [...,2,...]`  
1 IDENTIFIER OPTIONAL  
2 *inherits from \setupcombinedlist*

`\placefloat [...1] [...,2,...] {...3} {...4}`  
1 left right ~~here~~~~top~~ ~~bottom~~ ~~left~~ ~~right~~ ~~inmargin~~ ~~margin~~ ~~leftmargin~~ ~~rightmargin~~ ~~leftedge~~ ~~rightedge~~ ~~innermargin~~ ~~outermargin~~ ~~inneredge~~ ~~outeredge~~ ~~inner~~ ~~outer~~ ~~line~~ ~~high~~ ~~low~~ ~~fit~~ ~~page~~ ~~leftpage~~ ~~rightpage~~ ~~opposite~~ ~~always~~ ~~auto~~ ~~force~~  
tall reset line height depth split 90 180 270  
2 REFERENCE  
3 CONTENT  
4 CONTENT

`\placefootnotes [...,*,...]`  
\* inherits from \setupfootnotes

`\placeformula [...,1,...] {...2} $$3.$$`  
1 REFERENCE OPTIONAL OPTIONAL  
2 CONTENT  
3 DISPLAY MATH

`\placelegend {...1.} {...2.}`  
1 CONTENT  
2 CONTENT

`\placelist [...,1,...] [...,2,...]`  
1 IDENTIFIER OPTIONAL  
2 inherits from \setuplist

`\placelistoffloats`

`\placelistofsorts`

`\placelistofsynonyms`

`\placelocalfootnotes [...,*,...]`  
\* inherits from \setupfootnotes OPTIONAL

`\placelogos [...,*,...]`  
\* IDENTIFIER OPTIONAL

`\placeongrid [...1.] {...2.}`  
1 inherits from ~~onnew~~ ~~ongrid~~  
2 CONTENT

`\placeontopofeachother {...1.} {...2.}`  
1 CONTENT  
2 CONTENT

`\placereferencelist [...,*,...]`  
\* IDENTIFIER

`\placeregister [...1.] [...,2,...]`  
1 IDENTIFIER OPTIONAL  
2 inherits from \setupregister

`\placeregister [...,*,...]`  
\* inherits from \setupregister

`\placesidebyside {...1.} {...2.}`  
1 CONTENT  
2 CONTENT

`\placesubformula [...1,...] {...2} $$..3.$$`

1 REFERENCE                      OPTIONAL              OPTIONAL  
2 CONTENT  
3 DISPLAY MATH

`\position (...1,...) {...2}`

1 POSITION  
2 CONTENT

`\startpositioning ... \stop`

`\startpostponing ... \stop`

`\processblocks [...1,...] [...2,...]`

1 IDENTIFIER                      OPTIONAL  
2 IDENTIFIER

`\processpage [...1,...] [...2]`

1 IDENTIFIER  
2 yes no

`\startproduct ... \stop`

\* FILE NAME

`\startprofile [...*,...] ... \stop`

\* IDENTIFIER

`\program [...]`

\* IDENTIFIER

`\startproject ... \stop`

\* FILE NAME

`\publication [...]`

\* REFERENCE

`\startquotation [...*,...] ... \stop`

\* left middle right

`\quote {...}`

\* CONTENT

`\ran {...}`

\* CONTENT

`\ref [...1] [...2]`

1 t p r s e  
2 REFERENCE

`\reference [...1] {...2}`

1 REFERENCE  
2 CONTENT

`\referral [...,*,...]`

\* bet = TEXT  
ken = TEXT  
dat = TEXT  
van = TEXT  
aan = TEXT  
ref = TEXT

`\referraldate`

`\register [...1...] {...2.+...}`

1 TEXT OPTIONAL  
2 INDEX

`\reservefloat [...,1...] [...2.] [...3,...] {...4.}`

1 height = DIMENSION OPTIONAL OPTIONAL OPTIONAL  
width = DIMENSION  
frame = on off  
2 TEXT  
3 REFERENCE  
4 CONTENT

`\reset [...,*,...]`

\* IDENTIFIER

`\resetmarking [...]`

\* IDENTIFIER

`\resettextcontent [...1] [...2.] [...3.]`

1 top header text footer bottom OPTIONAL  
2 text margin edge  
3 lefttext middletext righttext

`\rightaligned {...}`

\* CONTENT

`\romannumerals {...}`

\* CONTENT

`\rotate [...,1...] {...2.}`

1 inherits from \setuprotate  
2 CONTENT

`\Romannumerals {...}`

\* CONTENT

`\scale [...,1...] {...2.}`

1 sx = NUMBER OPTIONAL  
sy = NUMBER  
2 CONTENT

`\screen`

`\section [...1,...] {...2.}`

1 REFERENCE OPTIONAL  
2 CONTENT

`\seeregister [...1] {...2.} {...3.+...}`

1 TEXT OPTIONAL  
2 CONTENT  
3 INDEX



```
\selectblocks [...,1...] [...,2...] [...,3.]
1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 criterium = all SECTION
```

```
\selectpaper [...,*,...]
* family = 1 2
```

```
\selectversion
```

```
\settextcontent [...,1.] [...,2.] [...,3.] [...,4.] [...,5.]
1 top header text footer bottom OPTIONAL OPTIONAL OPTIONAL
2 text margin edge
3 TEXT SECTION date MARK pagenumber
4 TEXT SECTION date MARK pagenumber
5 TEXT SECTION date MARK pagenumber
```

```
\setupalign [...,*,...]
* width left right middle inner outer wide broad height bottom line reset hanging nothanging hyphenated
nothyphenated lessshyphenation morehyphenation new old normal yes no flushleft flushright flushouter flushinner
center hz nohz spacing nospacing tolerant verytolerant stretch lefttoright righttoleft
```

```
\setuparranging [...,*,...]
* disable 2*16 2*8 2*4 2*2 2**2 2*2*4 2*4*2 2UP 2DOWN 2SIDE 2TOP mirrored rotated doublesided negative background 90
180 270
```

```
\setupbackground [...,*,...]
* leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
before = COMMAND
after = COMMAND
state = start stop
inherits from \setupframed
```

```
\setupbackgrounds [...,1.] [...,2...] [...,3...]
1 top header TEXT footer bottom pagepaper leftpage rightpage
2 leftedge leftmargin TEXT rightmargin rightedge
3 state = start stop cd:repeat
inherits from \setupframed
```

```
\setupblackrules [...,*,...]
* width = DIMENSION max
height = DIMENSION max
depth = DIMENSION max
alternative = a b
distance = DIMENSION
n = NUMBER
color = IDENTIFIER
```

```
\setupblank [...,*,...]
* normal default standard line halfline DIMENSION big medium small fixed flexible global unknown
```

```
\setupblock [...,1...] [...,2...]
1 IDENTIFIER
2 before = COMMAND
after = COMMAND
inner = COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
file = FILE
```

```
\setupbodyfont [...,*,...]
* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt ... 12pt
```

**\setupbodyfontenvironment** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>=</sub>...]

1 inherits from \definebodyfontenvironment OPTIONAL  
2 inherits from \definebodyfontenvironment  
3 inherits from \definebodyfontenvironment

**\setupbottom** [<sup>1</sup>...] [<sup>2</sup>...<sub>=</sub>...]

1 inherits from \setupheader  
2 inherits from \setupheader

**\setupbottomtexts** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 text margin edge OPTIONAL  
2 TEXT SECTION date MARK pagenumber  
3 TEXT SECTION date MARK pagenumber

**\setupbuffer** [<sup>1</sup>...] [<sup>2</sup>...<sub>=</sub>...]

1 IDENTIFIER OPTIONAL  
2 paragraph = NUMBER  
before = COMMAND  
after = COMMAND

**\setupbuttons** [<sup>1</sup>...<sub>=</sub>...]

\* state = start stop  
inherits from \setupframed

**\setupcapitals** [<sup>1</sup>...<sub>=</sub>...]

\* title = yes no  
sc = yes no

**\setupcaption** [<sup>1</sup>...] [<sup>2</sup>...<sub>=</sub>...]

1 IDENTIFIER  
2 inherits from \setupcaptions

**\setupcaptions** [<sup>1</sup>...<sub>=</sub>...]

\* location = top bottom none high low middle left middle right lefthanging righthanging leftmargin rightmargin  
innermargin outermargin  
width = fit broad max DIMENSION  
minwidth = fit DIMENSION  
headstyle = normal bold slanted boldslanted type cap small... COMMAND  
style = normal bold slanted boldslanted type cap small... COMMAND  
number = yes no none  
inbetween = COMMAND  
align = inner outer left right flushleft flushright middle center normal no yes  
conversion = numbers characters Characters romannumerals Romannumerals  
way = bytext bycd:section  
separator = TEXT  
stopper = TEXT  
command = COMMAND  
distance = DIMENSION

**\setupclipping** [<sup>1</sup>...<sub>=</sub>...]

\* state = start stop  
n = NUMBER  
nx = NUMBER  
ny = NUMBER  
x = NUMBER  
y = NUMBER  
sx = NUMBER  
sy = NUMBER  
width = DIMENSION  
height = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
offset = DIMENSION  
leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
mp = IDENTIFIER

`\setupcolor [...]`

\* IDENTIFIER

`\setupcolors [...,.*,...]`

\* state = start stop global local  
conversion = yes no always  
reduction = yes no  
rgb = yes no  
cmyk = yes no  
mpcmyk = yes no  
mpspot = yes no  
factor = yes no  
textcolor = IDENTIFIER  
split = c m y k p s no IDENTIFIER  
criterium = all none  
intent = none overprint knockout

`\setupcolumns [...,.*,...]`

\* n = ~~NUMBER~~<sup>OPTIONAL</sup>  
ntop = NUMBER  
rule = on off  
height = DIMENSION  
tolerance = verystRICT strict tolerant verytolerant stretch  
distance = DIMENSION  
balance = yes no  
align = text inner outer left right flushleft flushright middle center normal no yes  
blank = fixed halfline line flexible big medium small  
option = background  
direction = left right  
*inherits from* \setupframed

`\setupcombinations [...,.*,...]`

\* before = COMMAND  
inbetween = COMMAND  
after = COMMAND  
distance = DIMENSION  
height = DIMENSION fit  
width = DIMENSION fit  
location = top middle bottom left right  
align = inner outer left right flushleft flushright middle center normal no yes  
style = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER

`\setupcombinedlist [...,1.*,...2]`

1 IDENTIFIER  
2 level = 1 2 3 4 SECTION current  
*inherits from* \setuplist

`\setupcomment [...,.*,...]`

\* state = start stop  
width = DIMENSION  
height = DIMENSION  
color = IDENTIFIER  
title = TEXT  
space = yes no  
symbol = normal New Balloon Addition Help Paragraph Key IDENTIFIER  
option = max buffer  
margin = DIMENSION  
distance = DIMENSION

`\setupdescriptions [...1,...] [...2,...]`

```
1 IDENTIFIER OPTIONAL
2 style = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  width = fit broad DIMENSION
  distance = DIMENSION
  sample = TEXT
  text = TEXT
  closesymbol = TEXT
  closecommand = \...#1
  closesymbol = TEXT
  titleleft = TEXT
  titleright = TEXT
  titledistance = DIMENSION
  titlestyle = normal bold slanted boldslanted type cap small... COMMAND
  titlecolor = IDENTIFIER
  align = inner outer left right flushleft flushright middle center normal no yes
  margin = standard yes no DIMENSION
  location = left right top serried inmargin inleft inright hanging
  headstyle = normal bold slanted boldslanted type cap small... COMMAND
  headcolor = IDENTIFIER
  headcommand = COMMAND
  hang = fit broad NUMBER
  before = COMMAND
  inbetween = COMMAND
  after = COMMAND
  indentnext = yes no
  indenting = never none not no yes always first next small medium big normal odd even DIMENSION
  command = COMMAND
```

`\setupenumerations [...1,...] [...2,...]`

```
1 IDENTIFIER OPTIONAL
2 inherits from \setupdescriptions
```

`\setuexternalfigures [...*,...]`

```
* scale = NUMBER
  yscale = NUMBER
  yscale = NUMBER
  factor = max fit broad
  wfactor = NUMBER max broad fit
  hfactor = NUMBER max broad fit
  width = DIMENSION
  height = DIMENSION
  frame = on off
  preset = yes no
  display = FILE
  preview = yes no
  repeat = yes no
  object = yes no
  type = eps mps pdf tif png jpg mov cd:tex
  method = eps mps pdf tif png jpg mov cd:tex
  option = frame empty test
  frames = on off
  ymax = NUMBER
  xmax = NUMBER
  directory = TEXT
  location = local global default none
  maxwidth = DIMENSION
  maxheight = DIMENSION
  conversion = TEXT
  prefix = TEXT
```

`\setupfield [...1,...] [...2,...] [...3,...] [...4,...] [...5,...]`

```
1 IDENTIFIER
2 label horizontal vertical frame
3 inherits from \setupfields
4
5
```

```

\setupfields [...,1...] [...,2...] [...,3...] [...,4...]
1  reset label horizontal vertical frame
2  n          = NUMBER
    distance   = DIMENSION
    before     = COMMAND
    after      = COMMAND
    inbetween  = COMMAND
    color      = IDENTIFIER
    style      = normal bold slanted boldslanted type cap small... COMMAND
    align      = inner outer left right flushleft flushright middle center normal no yes
    option     = readonly required protected sorted unavailable hidden printable
    clickin    = REFERENCE
    clickout   = REFERENCE
    regionin   = REFERENCE
    regionout  = REFERENCE
    afterkey   = REFERENCE
    format     = REFERENCE
    validate   = REFERENCE
    calculate  = REFERENCE
    fieldoffset = DIMENSION
    fieldframecolor = IDENTIFIER
    fieldbackgroundcolor = IDENTIFIER
    inherits from \setupframed
3  inherits from \setupfields
4  inherits from \setupfields

```

```

\setupfillinlines [...,*...]
*  width      = DIMENSION
    margin    = DIMENSION
    distance  = DIMENSION
    before    = COMMAND
    after     = COMMAND

```

```

\setupfillinrules [...,*...]
*  width      = fit broad DIMENSION
    distance  = DIMENSION
    before    = COMMAND
    after     = COMMAND
    style     = normal bold slanted boldslanted type cap small... COMMAND
    n         = NUMBER
    interlinespace = small medium big
    separator  = TEXT

```

```

\setupfloat [...,1...] [...,2...]
1  IDENTIFIER
2  height      = DIMENSION
    width      = DIMENSION
    maxheight  = DIMENSION
    maxwidth   = DIMENSION
    minwidth   = DIMENSION
    default    = IDENTIFIER
    pageboundaries = LIST
    leftmargindistance = DIMENSION
    rightmargindistance = DIMENSION
    location   = left middle right
    inherits from \setupframed

```

```

\setupfloats [...,*,...]
*   location      = left right middle
    width         = fit DIMENSION
    before        = COMMAND
    after         = COMMAND
    margin        = DIMENSION
    spacebefore   = small medium big none
    spaceafter    = small medium big none
    sidespacebefore = small medium big none
    sidespaceafter = small medium big none
    indentnext    = yes no
    ntop          = NUMBER
    nbottom       = NUMBER
    nlines        = NUMBER
    default       = IDENTIFIER
    tolerance     = 0 1 2
    leftmargindistance = DIMENSION
    rightmargindistance = DIMENSION
    sidealign     = normal line
    numbering     = yes nocheck
    inherits from \setupframed

```

```

\setupfloatsplitting [...,*,...]
*   conversion = numbers characters Characters romannumerals Romannumerals
    lines      = NUMBER

```

```

\setupfonthandling [.1.] [.2.]
1  IDENTIFIER
2  inherits from \definefonthandling

```

```

\setupfontsynonym [.1.] [.2.]
1  IDENTIFIER
2  inherits from \definefontsynonym

```

```

\setupfooter [.1.] [...,2,...]
1  inherits from \setupheader
2  inherits from \setupheader

```

```

\setupfootertexts [.1.] [.2.] [.3.]
1  text margin edge OPTIONAL
2  TEXT SECTION date MARK pagenumber
3  TEXT SECTION date MARK pagenumber

```

```

\setupfootnotedefinition [...,*,...]
*   inherits from \setupdescriptions

```

```

\setupfootnotes [...,*,...]
*   conversion = numbers characters Characters romannumerals Romannumerals
    way        = bytext bycd:section
    location   = page TEXT columns firstcolumn lastcolumn high none
    rule       = on off
    before     = COMMAND
    after      = COMMAND
    width      = DIMENSION
    height     = DIMENSION
    bodyfont   = 5pt ... 12pt small big
    style      = normal bold slanted boldslanted type cap small... COMMAND
    distance   = DIMENSION
    columndistance = DIMENSION
    margindistance = DIMENSION
    n          = NUMBER
    numbercommand = \...#1
    textcommand  = \...#1
    split       = tolerant strict verystrict NUMBER
    textstyle   = normal bold slanted boldslanted type cap small... COMMAND
    textcolor   = IDENTIFIER
    interaction = yes no
    factor      = NUMBER
    inherits from \setupframed

```

```
\setupforms [...,*.,...]  
* method = HTML PDF
```

```
\setupformulas [...,*.,...]  
* location = left right  
left = TEXT  
right = TEXT  
align = inner outer left right flushleft flushright middle center normal no yes  
option = middle  
strut = yes no  
distance = DIMENSION  
margin = DIMENSION standard yes no  
align = flushleft flushright middle center  
leftmargin = DIMENSION  
rightmargin = DIMENSION  
indentnext = yes no  
alternative = IDENTIFIER  
spacebefore = DIMENSION  
after = DIMENSION  
separator = TEXT  
conversion = numbers characters Characters romannumerals Romannumerals TEXT
```

```
\setupframed [1.] [...,*2.,...]  
1 IDENTIFIER OPTIONAL  
2 height = fit broad DIMENSION  
width = fit broad fixed local DIMENSION  
autowidth = yes no force  
offset = none overlay default DIMENSION  
location = depth hanging high lohi low top middle bottom keep  
option = none empty  
strut = yes no global local  
align = inner outer left right flushleft flushright middle center normal no yes  
bottom = COMMAND  
top = COMMAND  
frame = on off none overlay  
topframe = on off  
bottomframe = on off  
leftframe = on off  
rightframe = on off  
frameoffset = DIMENSION  
framedepth = DIMENSION  
framecorner = round rectangular  
frameradius = DIMENSION  
framecolor = IDENTIFIER  
background = screen color none foreground IDENTIFIER  
backgroundscreen = NUMBER  
backgroundcolor = IDENTIFIER  
backgroundoffset = frame DIMENSION  
backgrounddepth = DIMENSION  
backgroundcorner = round rectangular  
backgroundradius = DIMENSION  
depth = DIMENSION  
corner = round rectangular  
radius = DIMENSION  
empty = yes no  
foregroundcolor = IDENTIFIER  
foregroundstyle = normal bold slanted boldslanted type cap small... COMMAND  
rulethickness = DIMENSION
```

```
\setupframedtexts [1.] [...,*2.,...]  
1 IDENTIFIER OPTIONAL  
2 bodyfont = 5pt ... 12pt small big  
style = normal bold slanted boldslanted type cap small... COMMAND  
left = COMMAND  
right = COMMAND  
before = COMMAND  
after = COMMAND  
inner = COMMAND  
linecorrection = on off  
depthcorrection = on off  
margin = standard yes no  
location = left right middle none  
indenting = never none not no yes always first next small medium big normal odd even DIMENSION  
inherits from \setupframed
```

```

\setuphead [...1,...] [...2,...]
1 SECTION
2 style = normal bold slanted boldslanted type cap small... COMMAND
  textstyle = normal bold slanted boldslanted type cap small... COMMAND
  numberstyle = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  textcolor = IDENTIFIER
  numbercolor = IDENTIFIER
  number = yes no
  ownnumber = yes no
  page = left right yes
  continue = yes no
  header = none empty high nomarking
  text = none empty high nomarking
  footer = none empty high nomarking
  before = COMMAND
  inbetween = COMMAND
  after = COMMAND
  alternative = normal inmargin middle TEXT
  hang = none broad fit line NUMBER
  command = \...#1#2
  numbercommand = \...#1
  textcommand = \...#1
  deepnumbercommand = \...#1
  deeptextcommand = \...#1
  prefix = + - TEXT
  placehead = yes no empty
  incrementnumber = yes no LIST FILE
  resetnumber = yes no
  file = IDENTIFIER
  expansion = yes no command
  margintext = yes no
  inherits from \setupheads

```

```

\setupheader [...1.] [...2,...]
1 TEXT margin edge OPTIONAL
2 state = normal stop start empty high none nomarking IDENTIFIER
  strut = yes no
  style = normal bold slanted boldslanted type cap small... COMMAND
  leftstyle = normal bold slanted boldslanted type cap small... COMMAND
  rightstyle = normal bold slanted boldslanted type cap small... COMMAND
  leftwidth = DIMENSION
  rightwidth = DIMENSION
  before = COMMAND
  after = COMMAND

```

```

\setupheadertexts [...1.] [...2.] [...3.]
1 text margin edge OPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber

```

```

\setupheadnumber [...1.] [...2.]
1 SECTION
2 NUMBER +cd:number -cd:number

```

```

\setupheads [...*,...]
* sectionnumber = yes NUMBER no
  alternative = normal margin middle TEXT paragraph
  separator = TEXT
  stopper = TEXT
  align = inner outer left right flushleft flushright middle center normal no yes
  aligntitle = yes float no
  tolerance = verystRICT strict tolerant verytolerant stretch
  indentnext = yes no
  command = \...#1#2
  margin = DIMENSION

```

```

\setupheadtext [...1.] [...2.]
1 nl fr en uk de es OPTIONAL
2 IDENTIFIER = TEXT

```

```

\setuphyphenmark [...*.]
* sign = -- --- - ( ) = /

```



`\setupindentations [...,1...] [...,2...]`

```
1 IDENTIFIER OPTIONAL
2 style = normal bold slanted boldslanted type cap small... COMMAND
  headstyle = normal bold slanted boldslanted type cap small... COMMAND
  width = fit DIMENSION
  text = TEXT
  sample = TEXT
  before = COMMAND
  after = COMMAND
  distance = DIMENSION
  separator = TEXT
```

`\setupindenting [...,*...]`

\* never none not no yes always first next small medium big normal odd even DIMENSION

`\setupinmargin [...,1...] [...,2...]`

```
1 left right NUMBER OPTIONAL
2 location = left right both
  style = normal bold slanted boldslanted type cap small... COMMAND
  before = COMMAND
  after = COMMAND
  align = inner outer left right flushleft flushright middle center normal no yes
  line = NUMBER
  distance = DIMENSION
  separator = TEXT
  width = DIMENSION
  distance = DIMENSION
  stack = yes no
  inherits from \setupframed
```

`\setupinteraction [...,*...]`

```
* state = start stop
  menu = on off
  page = yes no
  click = yes no
  split = yes no
  display = new
  openaction = REFERENCE
  closeaction = REFERENCE
  openpageaction = REFERENCE
  closepageaction = REFERENCE
  calculate = IDENTIFIER
  strut = yes no
  width = DIMENSION
  height = DIMENSION
  depth = DIMENSION
  style = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  contrastcolor = IDENTIFIER
  symbolset = IDENTIFIER
  title = TEXT
  subtitle = TEXT
  author = TEXT
  date = TEXT
  keyword = TEXT
  fieldlayer = auto IDENTIFIER
```

`\setupinteractionbar [...,*...]`

```
* state = start stop
  alternative = a b c d e f g
  symbol = yes no
  width = DIMENSION height fit
  height = DIMENSION height fit
  depth = DIMENSION
  color = IDENTIFIER
  step = NUMBER small medium big
  inherits from \setupframed
```

```

\setupinteractionmenu [...1,...] [...,2_,...]
1 IDENTIFIER
2 before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  left = COMMAND
  right = COMMAND
  middle = COMMAND
  state = start stop none local
  style = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  contrastcolor = IDENTIFIER
  distance = overlay DIMENSION
  samepage = yes empty no none
  unknownreference = yes empty no none
  leftoffset = DIMENSION
  rightoffset = DIMENSION
  topoffset = DIMENSION
  bottomoffset = DIMENSION
  position = yes no
  inherits from \setupframed

```

```

\setupinteractionscreen [...,*_,...]
* width = DIMENSION fit max
  height = DIMENSION fit max
  backspace = DIMENSION
  topspace = DIMENSION
  horoffset = DIMENSION
  veroffset = DIMENSION
  option = max fit doublesided singlesided auto none bookmark
  delay = NUMBER none

```

```

\setupinterlinespace [...,*_,...]
* height = NUMBER
  depth = NUMBER
  line = DIMENSION
  top = NUMBER
  bottom = NUMBER

```

```

\setupinterlinespace [...*]
* reset small medium auto big on off

```

```

\setupitemgroup [...1.] [...2.] [...,3,...] [...,4_,...]
1 IDENTIFIER OPTIONAL OPTIONAL OPTIONAL
2 NUMBER each
3 standard broad serried packed unpacked nowhite before after stopper joinedup atmargin inmargin autointro loose
  repeat SECTION paragraph intext random reverse
4 margin = no standard DIMENSION
  leftmargin = no standard DIMENSION
  rightmargin = no standard DIMENSION
  width = DIMENSION
  distance = DIMENSION
  factor = NUMBER
  items = NUMBER
  start = NUMBER
  before = COMMAND
  inbetween = COMMAND
  after = COMMAND
  left = TEXT
  right = TEXT
  beforehead = COMMAND
  afterhead = COMMAND
  headstyle = normal bold slanted boldslanted type cap small... COMMAND
  marstyle = normal bold slanted boldslanted type cap small... COMMAND
  symstyle = normal bold slanted boldslanted type cap small... COMMAND
  stopper = TEXT
  n = NUMBER
  symbol = NUMBER
  align = inner outer left right flushleft flushright middle center normal no yes
  symalign = left right flushleft flushright middle center
  indentnext = yes no

```

```
\setupitems [...,*,...]
* location = left right inmargin top bottom
symbol = 1 2 ... n a ... TEXT none
width = DIMENSION
n = NUMBER unknown
before = COMMAND
inbetween = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
after = COMMAND
```

```
\setuplabeltext [.1.] [.2.]
1 nl fr en uk de es optional
2 IDENTIFIER = TEXT
```

```
\setuplanguage [.1.] [...,.2,...]
1 nl fr en uk de es cz ..
2 inherits from \installlanguage
```

```
\setuplayout [...,*,...]
* width = DIMENSION fit middle
height = DIMENSION fit middle
backspace = DIMENSION
topspace = DIMENSION
margin = DIMENSION
leftmargin = DIMENSION
rightmargin = DIMENSION
header = DIMENSION
footer = DIMENSION
top = DIMENSION
bottom = DIMENSION
leftedge = DIMENSION
rightedge = DIMENSION
headerdistance = DIMENSION
footerdistance = DIMENSION
topdistance = DIMENSION
bottomdistance = DIMENSION
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
leftedgedistance = DIMENSION
rightedgedistance = DIMENSION
horoffset = DIMENSION
veroffset = DIMENSION
style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
marking = on off color screen TEXT page
location = left middle right bottom top singlesided doublesided
scale = DIMENSION
nx = NUMBER
ny = NUMBER
dx = DIMENSION
dy = DIMENSION
lines = NUMBER
columns = NUMBER
columnndistance = DIMENSION
grid = yes no
bottomspace = DIMENSION
cutspace = DIMENSION
textdistance = DIMENSION
textwidth = NUMBER
textmargin = DIMENSION
clipoffset = DIMENSION
page = IDENTIFIER
paper = IDENTIFIER
```

```
\setuplegend [...,*,...]
* n = NUMBER
distance = DIMENSION
inbetween = COMMAND
width = DIMENSION
height = DIMENSION
location = right bottom
bodyfont = 5pt ... 12pt small big
```

**\setuplinenumbering** [...,\*=,...]

\* conversion = numbers characters Characters romannumerals Romannumerals TEXT  
start = NUMBER  
step = NUMBER  
width = DIMENSION  
location = intext inmargin  
style = normal bold slanted boldslanted type cap small... COMMAND  
prefix = TEXT  
referencing = on off

**\setuplines** [...,\*=,...]

\* before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
indenting = never none not no yes always first next small medium big normal odd even DIMENSION  
space = yes no  
option = packed

**\setuplinewidth** [...]

\* DIMENSION

**\setuplist** [...,<sup>1</sup>...] [...,2,...]

1 IDENTIFIER  
2 state = start stop  
alternative = a b c ... none command  
coupling = on off  
criterium = SECTION local previous current here intro all  
pageboundaries = LIST  
style = normal bold slanted boldslanted type cap small... COMMAND  
numberstyle = normal bold slanted boldslanted type cap small... COMMAND  
textstyle = normal bold slanted boldslanted type cap small... COMMAND  
pagestyle = normal bold slanted boldslanted type cap small... COMMAND  
color = IDENTIFIER  
command = \...#1#2#3  
numbercommand = \...#1  
textcommand = \...#1  
pagecommand = \...#1  
interaction = cd:sectionnumber TEXT pagenumber all  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
left = TEXT  
right = TEXT  
label = yes no  
prefix = yes no none  
pagenumber = yes no  
headnumber = yes no  
cd:sectionnumber = yes no  
aligntitle = yes no  
margin = DIMENSION  
width = DIMENSION fit  
height = DIMENSION fit broad  
depth = DIMENSION fit broad  
distance = DIMENSION  
separator = TEXT  
stopper = TEXT  
symbol = none 1 2 3 ...  
expansion = yes no command  
maxwidth = DIMENSION  
*inherits from \setupframed*

**\setuplistalternative** [...,<sup>1</sup>] [...,2,...]

1 a b c  
2 command = COMMAND  
width = DIMENSION  
stretch = DIMENSION  
distance = DIMENSION

`\setupmakeup [1.] [2.,...]`

1 IDENTIFIER  
2 width = DIMENSION  
height = DIMENSION  
voffset = DIMENSION  
hoffset = DIMENSION  
page = left yes right  
commands = COMMAND  
doublesided = yes no empty  
headerstate = normal stop start empty none nomarking  
footerstate = normal stop start empty none nomarking  
textstate = normal stop start empty none nomarking  
topstate = stop start  
bottomstate = stop start  
pagestate = stop start  
color = IDENTIFIER

`\setupmarginblocks [...,*,...]`

\* location = inmargin left middle right  
style = normal bold slanted boldslanted type cap small... COMMAND  
width = DIMENSION  
align = inner outer left right flushleft flushright middle center normal no yes  
top = COMMAND  
inbetween = COMMAND  
bottom = COMMAND  
left = COMMAND  
right = COMMAND  
before = COMMAND  
after = COMMAND

`\setupmarginrules [.*]`

\* level = NUMBER  
rulethickness = DIMENSION

`\setupmarking [1.] [2.]`

1 IDENTIFIER  
2 state = start stop  
separator = COMMAND  
expansion = yes no

`\setupnarrower [...,*,...]`

\* left = DIMENSION  
right = DIMENSION  
middle = DIMENSION

`\setupnumbering [...,*,...]`

\* way = bytext bycd:section  
state = start stop

`\setupoppositeplacing [.*]`

\* state = start stop  
before = COMMAND  
inbetween = COMMAND  
after = COMMAND

`\setupoutput [...*,...]`

\* IDENTIFIER

`\setuppagenumber [...,*,...]`

\* number = NUMBER  
state = start stop keep

```

\setuppagenumbering [...,*,...]
*   alternative      = singlesided doublesided
    location         = header footer left right middle margin marginedge inleft inright
    conversion       = numbers characters Characters romannumerals Romannumerals
    style            = normal bold slanted boldslanted type cap small... COMMAND
    left             = TEXT
    right            = TEXT
    way              = bytext bycd:section
    text             = TEXT
    numberseparator  = TEXT
    textseparator    = TEXT
    cd:sectionnumber = yes no
    separator        = TEXT
    strut            = yes no
    state            = start stop
    width            = DIMENSION
    command          = \...#1

```

```

\setuppagetransitions [...,*,...]
*   reset NUMBER          OPTIONAL

```

```

\setuppalet [...]
*   IDENTIFIER

```

```

\setuppaper [...,*,...]
*   paper      = IDENTIFIER
    page       = IDENTIFIER
    nx         = NUMBER
    ny         = NUMBER
    width      = DIMENSION
    height     = DIMENSION
    topspace   = DIMENSION
    backspace  = DIMENSION
    option     = max fit
    method     = normal IDENTIFIER

```

```

\setuppapersize [...,1...] [...,2...]
1   A3 A4 A5 A6 letter ... CD IDENTIFIER LANDSCAPE mirrored rotated 90 180 270
2   negative inherits from \setuppapersize

```

```

\setupparagraphnumbering [...,*,...]
*   state      = start stop reset line
    style      = normal bold slanted boldslanted type cap small... COMMAND
    distance   = DIMENSION

```

```

\setupparagraphs [...,1.] [...,2.] [...,3*,...]
1   IDENTIFIER          OPTIONAL
2   NUMBER each
3   style              = normal bold slanted boldslanted type cap small... COMMAND
    width              = DIMENSION
    height             = DIMENSION
    align              = inner outer left right flushleft flushright middle center normal no yes
    tolerance          = verystRICT strict tolerant verytolerant stretch
    distance           = DIMENSION
    before             = COMMAND
    after              = COMMAND
    inner              = COMMAND
    command            = COMMAND
    rule               = on off

```

```

\setuppositioning [...,*,...]
*   state      = start overlay
    unit       = cm pt em mm ex es in
    factor     = NUMBER
    scale      = NUMBER
    offset     = yes no
    xstep      = absolute relative
    ystep      = absolute relative

```

```
\setupprofiles [...,*,...]
* option = test
```

```
\setupprograms [...,*,...]
* directory = TEXT
```

```
\setuppublications [...,*,...]
* alternative = apa normal
  inherits from \setupenumerations
```

```
\setupquote [...,*,...]
* before = COMMAND
  after = COMMAND
  style = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  location = TEXT margin
```

```
\setupreferencelist [...1...] [...2,...]
1 IDENTIFIER OPTIONAL
2 state = start stop
  criterium = SECTION local previous all
  command = COMMAND
  before = COMMAND
  after = COMMAND
```

```
\setupreferencing [...,*,...]
* state = start stop
  cd:sectionnumber = yes no
  prefix = + - TEXT
  interaction = label TEXT all symbol
  width = DIMENSION
  left = COMMAND
  right = COMMAND
  convertfile = yes no small big
  separator = TEXT
  autofile = yes no page
  global = yes no
  export = yes no
```

```
\setupregister [...1...] [...2...] [...3,...]
1 SINGULAR NAME OPTIONAL
2 IDENTIFIER
3 n = NUMBER
  balance = yes no
  align = inner outer left right flushleft flushright middle center normal no yes
  style = normal bold slanted boldslanted type cap small... COMMAND
  pagestyle = normal bold slanted boldslanted type cap small... COMMAND
  textstyle = normal bold slanted boldslanted type cap small... COMMAND
  indicator = yes no
  coupling = yes no
  cd:sectionnumber = yes no
  criterium = SECTION local all
  distance = DIMENSION
  symbol = 1 2 ... n a ... none
  interaction = pagenumber TEXT
  expansion = yes no command
  referencing = on off
  command = \...#1
  location = left middle right
  maxwidth = DIMENSION
  unknownreference = empty none
  alternative = a b A B
  prefix = both first none
  compress = no yes
  deeptextcommand = \...#1
```

```
\setuprotate [...,*,...]
* rotation = NUMBER
  location = normal high fit broad depth
  inherits from \setupframed
```

```
\setupscreens [...,.*,...]
* method      = dot rule external
  resolution  = NUMBER
  factor      = NUMBER
  screen      = NUMBER
```

```
\setupsection [.1.] [.2.] [...,2,...]
1 IDENTIFIER
2 IDENTIFIER
3 conversion    = numbers characters Characters romannumerals Romannumerals
previousnumber = yes no
```

```
\setupsectionblock [.1.] [...,2,...]
1 IDENTIFIER
2 number = yes no
page     = yes right
before   = COMMAND
after    = COMMAND
```

```
\setupsorting [.1.] [...,2,...]
1 IDENTIFIER
2 before = COMMAND
after    = COMMAND
command  = \...#1
state    = start stop
criterium = all used
style    = normal bold slanted boldslanted type cap small... COMMAND
expansion = yes no command
```

```
\setupspacing [...]
* broad packed
```

```
\setupstrut [...]
* yes no cap TEXT
```

```
\setupsubpagenumber [...,.*,...]
* way = bytext bycd:section
state = start stop none
```

```
\setupsymbolset [...]
* IDENTIFIER
```

```
\setupsynchronization [...,.*,...]
* state = start stop
```

```
\setupsynchronizationbar [...,.*,...]
* alternative = page local
width        = DIMENSION height fit
height       = DIMENSION
style        = normal bold slanted boldslanted type cap small... COMMAND
color        = IDENTIFIER
inherits from \setupframed
```

```
\setupsynonyms [.1.] [...,2,...]
1 IDENTIFIER
2 textstyle    = normal bold slanted boldslanted type cap small... COMMAND
synonymstyle   = normal bold slanted boldslanted type cap small... COMMAND
location      = left right top serried inmargin inleft inright
width         = DIMENSION
state         = start stop
criterium     = all used
conversion     = yes no
expansion      = yes no command
command       = \...#1#2#3
```



```
\setupsystem [...,*,...]
* resolution = NUMBER
  file       = TEXT
  directory  = TEXT
  random     = normal small medium big NUMBER
```

```
\setuptab [...,*,...]
* sample     = TEXT
  width      = DIMENSION
  headstyle  = normal bold slanted boldslanted type cap small... COMMAND
  location   = left right
```

```
\setuptables [...,*,...]
* distance   = small medium big
  bodyfont   = 5pt ... 12pt small big
  HL         = NUMBER small medium big none
  VL         = NUMBER small medium big none
  depth      = NUMBER strut
  height     = NUMBER strut
  rulethickness = DIMENSION
  rulecolor  = IDENTIFIER
  align      = inner outer left right flushleft flushright middle center normal no yes
  commands  = COMMAND
  align      = inner outer left right flushleft flushright middle center normal no yes
  background = screen color none
  backgroundscreen = NUMBER
  backgroundcolor = IDENTIFIER
  bodyfont   = 5pt ... 12pt small big
```

```
\setuptabulate [.1.] [...,*2,...]
1 IDENTIFIER OPTIONAL
2 unit = DIMENSION
  indenting = never none not no yes always first next small medium big normal odd even DIMENSION
  before    = COMMAND
  after     = COMMAND
  inner     = COMMAND
  EQ        = TEXT
  rulecolor = IDENTIFIER
  align     = inner outer left right flushleft flushright middle center normal no yes
  rulethickness = DIMENSION
  distance  = blank grid depth DIMENSION small medium big none
  bodyfont  = 5pt ... 12pt small big
  rule      = normal line
  split     = yes no
```

```
\setuptext [.1.] [...,*2,...]
1 inherits from \setupheader
2 inherits from \setupheader
```

```
\setuptextrules [...,*,...]
* location = left inmargin
  before   = COMMAND
  after    = COMMAND
  inbetween = COMMAND
  width    = DIMENSION
  distance = DIMENSION
  bodyfont = 5pt ... 12pt small big
  color    = IDENTIFIER
  style    = normal bold slanted boldslanted type cap small... COMMAND
  rulecolor = IDENTIFIER
```

```
\setuptexttexts [.1.] [.2.] [.3.]
1 text margin edge OPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber
```

```

\setupthinrules [.*.]
* interlinespace = small medium big
  n             = NUMBER
  before        = COMMAND
  inbetween     = COMMAND
  after         = COMMAND
  color         = IDENTIFIER
  backgroundcolor = IDENTIFIER
  height        = DIMENSION max
  depth         = DIMENSION max
  alternative   = a b c d
  rulethickness = DIMENSION
  color         = IDENTIFIER
  background    = color
  backgroundcolor = IDENTIFIER

```

```

\setuptolerance [...,*...]
* horizontal vertical stretch space verystrict strict tolerant verytolerant

```

```

\setuptop [.1.] [...,.2,...]
1 inherits from \setupheader
2 inherits from \setupheader

```

```

\setuptoptexts [.1.] [.2.] [.3.]
1 text margin edgeOPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber

```

```

\setuptype [...,*...]
* space = on off
  option = slanted normal none
  style  = normal bold slanted boldslanted type cap small... COMMAND
  color  = IDENTIFIER

```

```

\setuptyping [.1.] [...,.2,...]
1 file typing IDENTIFIER
2 space = on off
  page  = yes no
  option = slanted normal commands color none
  text  = yes no
  icommand = COMMAND
  vcommand = COMMAND
  ccommand = COMMAND
  before  = COMMAND
  after   = COMMAND
  margin  = DIMENSION standard yes no
  evenmargin = DIMENSION
  oddmargin = DIMENSION
  blank   = DIMENSION small medium big standard halflineline
  escape  = UNKNOWN MESSAGE
  space   = on off
  tab     = NUMBER yes no
  page    = yes no
  indentnext = yes no
  style   = normal bold slanted boldslanted type cap small... COMMAND
  color   = IDENTIFIER
  palet   = IDENTIFIER
  lines   = yes no hyphenated
  empty   = yes all no
  numbering = line file no
  bodyfont = 5pt ... 12pt small big
  strip    = no auto NUMBER

```

```

\setupunderbar [...,*...]
* alternative = a b c
  rulethickness = DIMENSION
  bottomoffset = DIMENSION
  topoffset    = DIMENSION
  rulecolor    = IDENTIFIER

```

```
\setupurl [...,*,...]
* style = normal bold slanted boldslanted type cap small... COMMAND
  urlalternative = none both before after
  urlspace = yes no
```

```
\setupversions [...,*,...]
* number = NUMBER
  style = normal bold slanted boldslanted type cap small... COMMAND
```

```
\setupwhitespace [...]
* none small medium big column fixed fix DIMENSION
```

```
\showbodyfont [...,*,...]
* inherits from \setupbodyfont
```

```
\showbodyfontenvironment [...,*,...]
* inherits from \setupbodyfont OPTIONAL
```

```
\showcolor [...]
* IDENTIFIER
```

```
\showcolorgroup [...1...] [...2,...]
1 IDENTIFIER
2 horizontal vertical name value NUMBER
```

```
\showexternalfigures [...,*,...]
* alternative = a b c OPTIONAL
```

```
\showfields [...,*,...]
* IDENTIFIER OPTIONAL
```

```
\showframe [...]
* TEXT marginPage
```

```
\showgrid [...1,...] {...2}
1 reset top bottom none all lines frame nonumber right left outer
2 CONTENT
```

```
\showlayout
```

```
\showmakeup
```

```
\showpalet [...1...] [...2,...]
1 IDENTIFIER
2 horizontal vertical name value
```

```
\showprint [...1,...] [...2,...] [...3,...]
1 inherits from \setuppapersize
2 inherits from \setuppapersize
3 inherits from \setuplayout
```

```
\showsetups
```

```
\showstruts
```

```
\showsymbolset [...]
* IDENTIFIER
```

`\somedline [...]`  
\* REFERENCE

`\somedhere {.^.^} {.^.^} [...]`  
1 CONTENT  
2 CONTENT  
3 REFERENCE

`\sort [...] {.^.^}`  
1 TEXT  
2 CONTENT

`\space`

`\splitfloat [...,.^.^] {.^.^} {.^.^}`  
1 inherits from \splitfloats  
2 CONTENT  
3 CONTENT

`\startregister [...] {.^.^} {.^.^}`  
1 TEXT  
2 INDEX

`\stretched {...}`  
\* WORD

`\sub [...,*,...]`  
\* REFERENCE

`\subject [...,.^.^] {.^.^}`  
1 REFERENCE  
2 CONTENT

`\subsection [...,.^.^] {.^.^}`  
1 REFERENCE  
2 CONTENT

`\subsubject [...,.^.^] {.^.^}`  
1 REFERENCE  
2 CONTENT

`\subsubsection [...,.^.^] {.^.^}`  
1 REFERENCE  
2 CONTENT

`\subsubsubject [...,.^.^] {.^.^}`  
1 REFERENCE  
2 CONTENT

`\switchtobodyfont [...,*,...]`  
\* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt ... 12pt  
small big

`\sym {...}`  
\* CONTENT

`\symbol [...] [...]`  
1 IDENTIFIER  
2 IDENTIFIER

```
\startsymbolset [...] ... \stop
* IDENTIFIER
```

```
\startsynchronization ... \stop
```

```
\synchronizationbar [.1.] [...,2,...]
1 IDENTIFIER
2 alternative = page local
   inherits from \setupsynchronizationbar
```

```
\synchronize
```

```
\synonym [.1.] {.2.} {.3.}
1 TEXT OPTIONAL
2 CONTENT
3 CONTENT
```

```
\tab {.1.} .2.
1 CONTENT
2 NOTHING
```

```
\starttable [...] ... \stop
* TEXT IDENTIFIER
```

```
\starttables [...] ... \stop
* TEXT IDENTIFIER
```

```
\starttabulate [.1.] [...,2,...] ... \stoptabulate
1 TEXT OPTIONAL OPTIONAL
2 inherits from \setupeexternalfigures
```

```
\tex {.*.}
* CONTENT
```

```
\textreference [.1.] {.2.}
1 REFERENCE
2 CONTENT
```

```
\textrule [.1.] {.2.}
1 top bottom OPTIONAL OPTIONAL
2 CONTENT
```

```
\thinrule
```

```
\thinrules [.1.]
* inherits from \setupthinrules
```

```
\title [...,1...] {.2.}
1 REFERENCE OPTIONAL
2 CONTENT
```

```
\tooltip [.1.] {.2.} {.3.}
1 left right middle
2 CONTENT
3 CONTENT
```

```
\translate [...,*...]
* IDENTIFIER = TEXT
```

```
\typ {...}
*   CONTENT
```

```
\type {...}
*   CONTENT
```

```
\typebuffer [...]
*   IDENTIFIER
```

```
\typefile [.1.] {.2.}
1   IDENTIFIEROPTIONAL
2   CONTENT
```

```
\starttyping ... \stoptyping
```

```
\underbar {...}
*   CONTENT
```

```
\underbars {...*...}
*   WORD
```

```
\startunpacked ... \stop
```

```
\useblocks [...,1...] [...,2...]
1   IDENTIFIER          OPTIONAL
2   IDENTIFIER
```

```
\usecommands {...}
*   CONTENT
```

```
\usedirectory [...,*...]
*   IDENTIFIER reset
```

```
\useencoding [...,*...]
*   IDENTIFIER
```

```
\useexternaldocument [.1.] [.2.] [.3.]
1   IDENTIFIER
2   file
3   TEXT
```

```
\useexternalfigure [.1.] [.2.] [.3.] [.,.4.,...]
1   IDENTIFIER          OPTIONAL          OPTIONAL          OPTIONAL
2   FILE
3   IDENTIFIER
4   inherits from \setupexternalfigures
```

```
\useexternalfile [.1.] [.2.] [.3.] [.,.4.,...]
1   IDENTIFIER
2   IDENTIFIER
3   FILE
4   bodyfont = 5pt ... 12pt small big
```

```
\useexternalfiles [.1.] [.,.2.,...]
1   IDENTIFIER
2   bodyfont = 5pt ... 12pt small big
    file      = FILE
```

\useexternalsoundtrack [.1.] [.2.]

- 1 IDENTIFIER
- 2 FILE

\usemodule [...,\*...]

- \* IDENTIFIER

\useresources [...,\*...]

- \* FILE

\usespecials [...,\*...]

- \* reset IDENTIFIER

\usesymbols [...\*...]

- \* IDENTIFIER

\usetypescript [...<sup>1</sup>...;...] [...<sup>2</sup>...;...] [...<sup>3</sup>...;...]

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 IDENTIFIER

\usetypescriptfile [...,\*...]

- \* FILE

\useURL [.1.] [.2.] [.3.] [.4.]

- 1 IDENTIFIER
- 2 TEXT
- 3 file
- 4 TEXT

\version [...\*...]

- \* final concept temporary

\vl [...\*...]

- \* NUMBER

\weekday {...\*...}

- \* CONTENT

\whitespace

\wordright {...\*...}

- \* CONTENT

\writebetweenlist [.1.] {...\*...}

- 1 SECTION IDENTIFIER
- 2 CONTENT

\writetolist [.1.] {...\*...} {...\*...}

- 1 SECTION IDENTIFIER
- 2 CONTENT
- 3 CONTENT

\writetoreferencelist [.1.] {...\*...} {...\*...}

- 1 IDENTIFIER
- 2 CONTENT
- 3 CONTENT

\writetoregister [<sup>1</sup>...] [<sup>2</sup>] {...<sup>3</sup>+...}  
1 SINGULAR NAME OPTIONAL  
2 TEXT  
3 INDEX

\WEEKDAY {...}  
\* CONTENT

\Word {...}  
\* WORD


\Words {... \* ...}  
\* WORD

\WORD {...}  
\* WORD

\WORDS {... \* ...}  
\* WORD







**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**